

(No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China)

JBC40 L1 Concrete mixer pump



#### Optional:



Without Chassis



Without Batcher

#### 1. Description:

Concrete mixer pump is combined by the traditional concrete pump and the mixer together. It achieves full automatic during concrete construction process.

#### 2. Application:

Convey floor heating lightweight foamed cement, mortar, fine aggregate concrete.

Convey greening soil in ecological environment construction.

Convey all kinds of engineering construction in the plain concrete, fiber concrete.

Most suitable for four to six floor buildings, especially in the group buildings, bridges and the small construction sites where need the concrete mixer at the scene.

#### 3. Features:

Weichai 100KW Generator

Mixer and pump in one machine.

Transfer concrete through pipeline. It is fast and safe.

It has small size and suitable for more special environment.

Optional part: Hydraulic leg, Telescopic rail, Cement boom. This is easy to operate.

Flexible mixer and batch: Original creation, Keep truck balance in center, convenient maintenance.

Version: 2015 Copyright © Gaode Equipment Co., Ltd.



(No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China) Batcher: Increase the feeding speed and production efficiency.

Cement hanger: Reduce labor intensity and save manpower.

### 4. Technical data

Pumping system	
Max. theoretical Pumping Output	40m3/h
Delivery Pressure	28Mpa
Outlet Pressure	7Mpa
Max. Conveying Distance (Horizontal)	300m
Max. Conveying Distance (Vertical)	70m
Type of Distribution Valve	S valve
Main motor	37Kw
Generator	Weichai 100Kw
Voltage	380V
Main Oil Pump	Domestic / Kawasaki 112
Delivery cylinder * stoke	200*1000mm
Main oil cylinder/ rod * stroke	100/70*1000mm
Oil tank capacity	300L
Discharge hopper capacity	600L
Concrete outlet diameter	200mm
Diameter of delivery pipe	125mm
Mixing system	
Mixer type	JS350
Max. theoretical mixing Output	18m3/h
Hpper capacity	800L
Mixing motor power	15Kw
Hoist motor	4.5Kw

Version: 2015



Water pump	0.75Kw	
Max. aggregate size	Cobblestone 40mm Gravel 30mm	
Materials filling height	1200mm	
Batching system		
Hopper capacity	1.2*2 m3	
Hydraulic outrigger	2pcs	
Load cell	8pcs	
Operation interface	Touch screen in English	
Compressor	3bar	
Flexible	Yes (manually)	
Mini printer	1pc	
Wireless remote control	yes	
The whole machine		
Total weight	8500KG	
Size (Without batcher)	7300*2210*2580mm	
Size (Driving with batcher)	8400**2210*2580mm	
Size (Working with batcher)	10200**2210*2580mm	

## 5. Usage

Concrete mixer pump used in horizontal pumping

Version: 2015

# Gaode Equipment CO., LTD. (No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China)





Copyright © Gaode Equipment Co., Ltd. Version: 2015





Concrete mixer pump in vertical pumping







Version: 2015