




郑州高德机械设备有限公司 Gaode Equipment Co., Ltd.

地址 ADD: 郑州市金水区丰庆路 4 号院 14 号楼 9 号 邮编 P.C.:450053
No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China
网站 (Web) :www.gaodetec.com E-Mail: info@gaodetec.com
电话 TEL.:+86-371-55951210 传真 FAX:+86-371-55951210

GF25 cement foam concrete unit



Working principle:

GF25 foaming cement machine put cement and water into a slurry mixing and then mix them in a certain proportion, press them into transmission pipelines through hydraulic cylinder; According to a certain proportion foam mixed with water and then mixed with compressed air by the high-pressure pump; In the pipeline it form the high-density foam and meticulous, at last form the foam cement with the slurry in the pipeline.

Features:

1. Adopting double cylinder hydraulic push mechanism to pump lightweight concrete, flux is stable, and wave is small.
2. Proportion of mixture is controlled automatically, so the density of lightweight concrete can be adjusted easily.
3. Adopting selected matching components, it also has reliable quality and good after-sales service.
4. We can also use good domestic foaming agent to reduce the construction cost.
5. With road wheel and universal wheel, the machine is flexible with moving and positioning.
6. Hydraulic system cooling use air cooling instead of water cooling, this make it more convenient as there's no need to drain pipe.
7. Electrical appliance box is equipped with remote control handle; all functions can be operated by remote control handle.
8. It can be used in vehicle.



郑州高德机械设备有限公司
Gaode Equipment Co., Ltd.

地址 ADD: 郑州市金水区丰庆路 4 号院 14 号楼 9 号 邮编 P.C.:450053
 No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China
 网站 (Web) :www.gaodetec.com E-Mail: info@gaodetec.com
 电话 TEL.:+86-371-55951210 传真 FAX:+86-371-55951210

Technical data:

Model	GF25
Max.Output	25m ³ /h
Max.Conveying Pressure	3 MPa
Max.Horizontal Transporting Range	300 m
Max. Vertical Transporting Height	120 m
Acceptable Max. Aggregates size	8 mm
Power	30KW
Dimension	3800x1500x1500mm
Weight	1700kg

A complete set of GF25 foam concrete machine:

No.	Item	Specification	Qty.	Unit	Remark
1	Foam concrete pump		1	set	
2	Foam concrete mixer		1	set	
3	Feeder		1	set	
4	Water pump	WQ6-16-0.75	1	set	
5	Foaming agent		200	Kg	
6	Conveying hose	∅ 64×10m	8	PCS	Max. pressure 4Mpa
7	Inlet hose	∅ 125	1	PCS	
8	Clamp	125A	4	PCS	
		100A	3	PCS	
		70A	9	PCS	
		51A	6	PCS	
9	Gasket	125A	10	PCS	
		100A	10	PCS	
		70A	18	PCS	
		51A	12	PCS	
10	Accessories		1	set	



郑州高德机械设备有限公司 Gaode Equipment Co., Ltd.

地址 ADD: 郑州市金水区丰庆路 4 号院 14 号楼 9 号 邮编 P.C.:450053
No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China
网站 (Web) :www.gaodetec.com E-Mail: info@gaodetec.com
电话 TEL.:+86-371-55951210 传真 FAX:+86-371-55951210

Detailed image:

Foam concrete pump:



Foam concrete mixer and feeder:





郑州高德机械设备有限公司 Gaode Equipment Co., Ltd.

地址 ADD: 郑州市金水区丰庆路 4 号院 14 号楼 9 号 邮编 P.C.:450053
No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China
网站 (Web) :www.gaodetec.com E-Mail: info@gaodetec.com
电话 TEL.:+86-371-55951210 传真 FAX:+86-371-55951210

Foaming agent:

The foaming agent is a high-tech product, it has the characteristics as high expansion ratio, balanced density, foaming stability, and a long continuance, etc. Thus it is an environmental protective mighty foaming agent, which is nuisance-free and pollution-free.



Application:

1. Applied for insulating layer in floor heating constructions: the surface will flow smooth naturally and is an essential advanced equipment for floor heating construction.
2. Applied for roof insulation constructions: The foam material used in roof insulation is with warm keeping, heat insulating function, it's effect is 20-30 times the ordinary material, which keeps the room temperature of top floor the same as other floors, warm in winter and cool in summer.
3. Can be used in producing various specifications of cement foam board, cement foam bricks and external wall insulation material.
4. Can be used in filling tunnel and mine internal voids, etc. And applied for insulation of low temperature cold store and refrigerated depot section.
5. Applied in freezing prevention and temperature maintenance of pipeline.



郑州高德机械设备有限公司
Gaode Equipment Co., Ltd.

地址 ADD: 郑州市金水区丰庆路 4 号院 14 号楼 9 号 邮编 P.C.:450053
No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China
网站 (Web) :www.gaodetec.com E-Mail: info@gaodetec.com
电话 TEL.:+86-371-55951210 传真 FAX:+86-371-55951210



[Ms Caroline Wu](#)

Assistant of Sales Manager

Import & Export Department

Gaode Equipment Co.,Ltd.

Mobile:15515723617

Tel:+86-371-55951210 Fax:+86-371-63526676

[Skype:caroline72](#)

[Email:caroline@gaodetec.com](mailto:caroline@gaodetec.com)

Web: www.gaodetec.com www.foamconcreteequipment.com