


2GP SERIES PNEUMATIC GROUT PUMPS

2GP series pneumatic grout pumps are driven by compressed air, thus this pump can safely use in the large water drenching and high gas/firedamp places. It can be blocked for a long time and has no heating problem. This pump transmits pressure signals by working medium (slurry and compressed air) to form closed-loop automatic control function, therefore the pump is simple in structure, can regulate timely and accurately, and has no overpressure problem. The shift device of this pump has feature with air pressure automatic location, thus this pump works with safety and reliability. This pump has the function of automatic regulating output according to the pre-seted grouting final pressure. The pump can grout simple-liquid, dual-liquid and chemical grout.

1. Performance Curve



2.	Technical	Sheet

Technical Sheet						
0.5m³ ,0.7m³(portable) , 1.5m³ pneumatic dual-slurry grout pump,3.0m³ pneumatic dual-slurry grout pump						
air consumption (m ³ /min)	air pressure (MPa)	overall dimension(m) weight (kg)	Slurry and Sodium silicate ratio		
0.5	0.2~0.63	0.6x0.3x0.4	18	1:1		
0.7		0.8x0.4x0.7	41	1:1~1:0.75		
1.5		1.3x0.5x1.0	83	1:1~1:0.5		
3	<u> </u>	1.3x0.6x1.2	110	1:1~1:0.5		
Accessories	Suction hose, filter, delivery hose, junction device, tools, sealing parts bit. Optional: thickness slurry hopper, hole plug, mixture ratio regulator, baume gauge.					
air consumption (m ³ /min)	Model	Rated ou	utput	Rated pressure(MPa)		
		L/min	M3/h			
0.5m³(portable)	2GP10/5	10	0.6	5		
0.7m ³ (portable)	☆2GP50/4	50	3.0	4		
	☆2GP24/10	24	1.44	10		
1.5m³	☆2GP130/3	130	7.8	3.5		
	☆2GP96/5	96	5.78	5		
	☆2GP70/7	70	4.2	7		
	☆2GP40/11	40	2.4	11		
3.0m³	☆2GP150/6	150	9.0	6		
	☆2GP110/8	110	6.6	8		
	☆2GP80/11	80	4.8	11		
	☆2GP50/19	50	3.0	19		
	☆2GP30/30	30	1.8	30		


Those which marked with " \precsim " are commonly grout pump types in coal mine , and have passed MA certificate.

3. <u>Certificates</u>

CE AND ISO9001-2008







Version: Aug.2014

Copyright©Gaode Equipment Co., Ltd.



2GP SERIES, the compressed air consumption 1.5m3/min,3m3/min



2GP50/4, 2GP24/10



2GP30/30

2GP SERIES GROUT PUMPS









Gaode grout pump