

(No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China)

JBC40 L2 Concrete mixer pump



Optional:



Without Chassis



Without Batcher

1. Description:

Concrete mixer pump is combined by the traditional concrete pump and the mixer together. It achieves full automatic during concrete construction process.

2. Application:

Convey floor heating lightweight foamed cement, mortar, fine aggregate concrete.

Convey greening soil in ecological environment construction.

Convey all kinds of engineering construction in the plain concrete, fiber concrete.

Most suitable for four to six floor buildings, especially in the group buildings, bridges and the small construction sites where need the concrete mixer at the scene.

3. Features:

Mixer and pump in one machine.

Transfer concrete through pipeline. It is fast and safe.

It has small size and suitable for more special environment.

Optional part: Hydraulic leg, Telescopic rail, Cement boom. This is easy to operate.

Batcher: Increase the feeding speed and production efficiency.

Cement hanger: Reduce labor intensity and save manpower.

Version: 2015 Copyright © Gaode Equipment Co., Ltd.



4. Technical data

Pumping system	
Max. theoretical Pumping Output	40m3/h
Delivery Pressure	28Mpa
Outlet Pressure	7Мра
Max. Conveying Distance (Horizontal)	300m
Max. Conveying Distance (Vertical)	70m
Type of Distribution Valve	S valve
Main motor	37Kw
Generator	Yuchai100Kw
Voltage	380V
Main Oil Pump	Domestic / Kawasaki 112
Delivery cylinder * stoke	200*1000mm
Main oil cylinder/ rod * stroke	100/70*1000mm
Oil tank capacity	300L
Discharge hopper capacity	600L
Concrete outlet diameter	200mm
Diameter of delivery pipe	125mm
Mixing system	
Mixer type	JS500
Max. theoretical mixing Output	28m3/h
Hopper capacity	800L
Mixing motor power	18.5Kw
Hoist motor	5.5Kw
Water pump	0.75Kw
Max. aggregate size	Cobblestone 40mm
	Gravel 30mm
Materials filling height	1200mm

Version: 2015 Copyright © Gaode Equipment Co., Ltd.



Flexible	Yes	
Batching system		
Hopper capacity	1.2*2 m3	
Hydraulic outrigger	2pcs	
Load cell	8pcs	
Operation interface	Touch screen in English	
Compressor	3bar	
Flexible	Yes (manually)	
Mini printer	1pc	
Wireless remote control	yes	
The whole machine		
Total weight	8500KG	
Size (Without batcher)	7300*2210*2580mm	
Size (Driving with batcher)	8400**2210*2580mm	
Size (Working with batcher)	10200**2210*2580mm	

5. Usage

Concrete mixer pump used in horizontal pumping

Version: 2015







Concrete mixer pump in vertical pumping

Version: 2015 Copyright © Gaode Equipment Co., Ltd.



(No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China)



郑州高德机械设备有限公司

Gaode Equipment Co., Ltd.
No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District,
Zhengzhou, Henan China

P.C. 450053

Tel: +86-371-55951210 Fax: +86-371-55951210 Email: info@gaodetec.com Website: www.gaodetec.com

Version: 2015 Copyright © Gaode Equipment Co., Ltd.