



Gaode Equipment CO., LTD.

(No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China)

JBT40 L1 Trailer concrete pump with forced mixer



1. Description:

Trailer concrete pump with forced mixer is combined by the traditional concrete pump and the mixer together. It achieves full automatic during concrete construction process.

2. Application:

Convey floor heating lightweight foamed cement, mortar, fine aggregate concrete.

Convey greening soil in ecological environment construction.

Convey all kinds of engineering construction in the plain concrete, fiber concrete.

Most suitable for four to six floor buildings, especially in the group buildings, bridges and the small construction sites where need the concrete mixer at the scene.

3. Features:

1. Innovation, mixer can be pushed and pulled, moving more safely.
2. Transfer concrete through pipeline. It is fast and safe.
3. It has small size and suitable for more special environment.
4. Optional part: cement boom, wireless remote control. This is easy to operate.
5. Compulsive mixing, high quality, high efficiency.
6. Optional batching machine, setting up the materials faster, Well-proportioned and efficient.



Gaode Equipment CO., LTD.

(No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China)

4. Technical data

| | |
|---|----------------------------------|
| Parameters | JBT40 L1 |
| Main oil pump | Domestic / Kawasaki 112 |
| Mixer model | JS 350 |
| The maximum theoretical delivery output | 40 m ³ /h |
| The maximum theoretical mix output | 18 m ³ /h |
| Vertical pumping distance | 70m |
| Horizontal pumping distance | 300m |
| Main oil cylinder / Rod * Stroke | 100*70*800 |
| Distribution valve type | S valve |
| Main motor | 37kw |
| Outlet pressure | 8Mpa |
| Hydraulic system type | Open system |
| Oil Cylinder * Rod * Stroke | 100*70*100 |
| Delivery Cylinder * Stroke | 200*1000 |
| Hopper Capacity * Filling Height | 600*1050 |
| Motor voltage | 380V |
| Hoist motor | 5.5kw |
| Mixing motor | 15kw |
| Diameter of outlet | 180mm |
| Max. aggregate size | Pebble 40mm; Crushed stone:30 |
| Weight | 5300kg |
| Dimension | 4960*2100*2500mm |



Gaode Equipment CO., LTD.

(No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China)

5. Usage

Trailer concrete pump with mixer used in horizontal pumping



Trailer concrete pump with mixer used in vertical pumping

