

GH100-915B super high pressure hose pump

Hose pump consists mainly of pump house, rotor, roller, idle roller, squeeze tube and driving unit. The squeeze hose is U-shape in pump house, when rotor drives roller to rotate, hose is deformed. After the roller rotate, the deformed hose recover by its elasticity. Thus the negative pressure in this hose is generated, sucking slurries, and discharging through outlet under roller's push, finally forms pressure conveying of slurries. GH100-915B super high pressure hose pump adopts special process squeeze hose, working pressure could be up to 26bar.



Features:

- ★No Seals, No valves
- ★Self-priming
- ★Only tube to replace
- ★ Dry-running without damage
- ★Reversible
- ★No contact between product and mechanical parts
- ★Able to pump products with solid parts inside
- ★Easy maintenance, low-cost, short down time.





地址 ADD: 郑州市金水区丰庆路 4 号院 14 号楼 9 号 邮编 P.C.:450053 No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China 网站(Web):www.gaodetec.com E-Mail: info@gaodetec.com 电话 TEL.:+86-371-55951210 传真 FAX:+86-371-55951210

Technical Data

Output	30m3 / h
Max. Pressure	26 bar
Squeeze Hose ID	100mm
Revolution Speed	32RPM
Max. Aggregate Size	3mm
Max. Suction Lift	5m
Motor Power	45 KW
Weight	1750kg

Product Detail



Nice quality electric control box



Helical Bevel Gear Units for Reducer

Gaode Equipment Co., Ltd.

No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China P.C. 450053 **Tel:** +86-371-55951660/55090762/55951210 **Mobile/WhatsApp/Viber**: +86-13939067523 **Fax:** +86-371-63526676 **Email:** info@gaodetec.com **Website:** www.gaodetec.com