



GAODETEC

郑州高德机械设备有限公司

Gaode Equipment Co., Ltd.

地址 ADD: 郑州市金水区丰庆路 4 号院 14 号楼 9 号

邮编 P.C.:450053

No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China

网站 Web: www.gaodetec.com

邮箱 E-Mail: info@gaodetec.com

电话 TEL.:+86-371-55951660

GZ-3AR Refractory Gunite Machine





郑州高德机械设备有限公司

Gaode Equipment Co., Ltd.

地址 ADD: 郑州市金水区丰庆路 4 号院 14 号楼 9 号 邮编 P.C.:450053
No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China
网站 Web: www.gaodetec.com 邮箱 E-Mail: info@gaodetec.com
电话 TEL.:+86-371-55951660

Description

GZ-3AR Refractory Guniting Machine is specifically designed for refractory dry-mix shotcrete gunning applications with air motor drive. With this LZ-3AR, you can get low dust, low bound and high performance spraying flow in nozzle.

Application

It can be used for refractory spraying applications, as well as for concrete shotcrete application.

GZ-3AR Refractory Guniting Machine is widely used for spraying refractory materials, castable in steel plant. Equipped with ABB frequency converter could achieve variable output from 1m³/h to 3m³/h.

Features

1. Variable Output. 5 cylinders piston air motor drive
2. Bag cutter and flat hopper with vibrator
3. Collect dust bag
4. Clean dust gun
5. Heavy-duty solid wheels
6. Coupling and clamp
7. Light weight nozzle
8. Blast rubber hose



郑州高德机械设备有限公司

Gaode Equipment Co., Ltd.

地址 ADD: 郑州市金水区丰庆路 4 号院 14 号楼 9 号 邮编 P.C.:450053
No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou, Henan China
网站 Web: www.gaodetec.com 邮箱 E-Mail: info@gaodetec.com
电话 TEL.:+86-371-55951660

Technical Data

Rated Output	1-3m ³ /h (2-6 ton/h)
Max. Horizontal Conveying Distance	200m
Max. Aggregate Size	Φ10 mm
Conveying Hose Inner Diameter	38mm
Operating air Pressure	0.2-0.4MPa(29-58PSI)
Air Consumption	10-11m ³ /min
Engine	4kw
Material Charging Height	1.1m
Rotor Speed	13.2r/min
Overall Dimension(L×W×H)	1.13×0.54×1.1m
Weight	430kg