

GZ-3 Dry-mix Shotcrete Machine

1. GZ-3 shotcrete machine description:

GZ-3 Shotcrete machine/Gunite machine /Concrete Spraying Machine is small-sized shotcrete machine for the dry spraying process.

GZ-3 shotcrete machine can be used as well for small jobs, such as joint filling, swimming pool, refractory application and extensive slope consolidation work, etc.

GZ-3 shotcrete machine is available in following versions:

Basic: electric drive can be combined with tyre chassis

Extended (optional): air motor or diesel drive combined skid or rail-wheel

2. GZ-3 shotcrete machine technical parameters:

Electric Motor Driven

Output Capacity	$3m^3/h$		
Max. Horizontal Conveying Distance	200m		
Suitable Mix Ratio(Cement/Sand)	≤1:3~5		
Max. Aggregate Size	Ф10 mm		
Conveying Hose Inner Diameter	Ф38/Ф50mm		
Conveying Pressure	0.2-0.4MPa(29-58PSI)		
Air Consumption for conveying material	5~6m ³ /min(180-215CFM)		
Material Charging Height	0.9m		
Rotor Speed	14r/min		
Motor Power	3kW(4hp),IP55		
Available Voltage	220V,380V,440V,660V 50Hz/60Hz		
Overall Dimension(length×width×height)	1.13×0.54×1.02m		
Net Weight	430kg		

Air Motor Driven

Output Capacity	1.5-3m ³ /h		
Max. Horizontal Conveying Distance	200m		
Suitable Mix Ratio(Cement/Sand)	≤1:3~5		
Max. Aggregate Size	Ф10 mm		
Conveying Hose Inner Diameter	Ф50mm		
Conveying Pressure	0.2-0.4MPa(29-58PSI)		
Air Consumption for conveying material	5~6m ³ /min(180-215CFM)		
Air Motor Air Pressure	0.5MPa(71PSI)		
Material Charging Height	0.9m		

Version: Aug.2012 Copyright@Gaode Equipment Co., Ltd.

Rotor Speed	14r/min	
Air Motor Type	TMH3.2	
Air Motor Air Consumption	4.8m ³ /min(171CFM)	
Overall Dimension(length×width×height)	1.13×0.54×1.02m	
Net Weight	430kg(947lbs)	

Diesel driven:

Rated Output	2-3m 3 /h		
Max. Horizontal Conveying Distance	200m		
Suitable Mix Ratio(Cement/Sand)	≤ 1: 3~5		
Max. Aggregate Size	Φ 10 mm		
Conveying Hose Inner Diameter	38/51mm		
Operating air Pressure	0.2-0.4MPa(29-58PSI)		
Air Consumption	5~6m 3 /min(180-215CFM		
Diesel Engine	10hp,2200rpm		
Diesel Engine Starting	Electric start		
Clutch Type in Diesel Engine	Automatic Clutch		
Material Charging Height	0.9m		
Rotor Speed	9-13r/min		
Overall Dimension(L× W× H)	1.8× 0.8× 1.2m		
Net Weight	480kg		

Certificate:

CE AND ISO9001-2008





A complete set of GZ-3 shotcrete machine:

No.	Description	Quantity	Unit	Remarks
1	GZ-3 Main Machine	1	set	
2	Nozzle Assy.	1	set	
3	Conveying Hose, ID38mm, 50ft.Length	1	piece	
4	Water hose with hose hoop	1	piece	
5	Rubber Hose Joint(long)	1	piece	Fitting
6	Rubber Hose Joint(short)	2	piece	Fitting
7	Quick Coupling	3	piece	
8	Upper Sealing Plate	1	piece	
9	Lower Sealing Plate	1	piece	

Picture:

Electric drive:



Version: Aug.2012 Copyright@Gaode Equipment Co., Ltd.

Air motor drive:





Application:





Gaode Equipment Co., Ltd.

Add: No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou,

Henan China P.C.: 450000

Tel: +86-371-55951210 Fax: +86-371-63526676 Email: info@gaodetec.com Web: www.gaodetec.com

Version: Aug.2012 Copyright@Gaode Equipment Co., Ltd.