

# **GZ-9 Dry-mix Shotcrete Machine**

## 1. GZ-9 shotcrete machine description:

GZ-9 is large-sized shotcrete machine for the spraying process.

GZ-9 can be used for large-section tunnel building, mine, etc

GZ-9 is available in following versions:

Basic: electric drive can be combined with tyre chassis

Extended (optional): Air motor drive or diesel drive combined with Skid or

Rail-wheel

## 2. GZ-9 shotcrete machine technical parameters:

#### **Electric drive:**

Output Capacity	$9\text{m}^3/\text{h}$		
Max. Horizontal Conveying Distance	200m		
Suitable Mix Ratio(Cement/Sand)	≤1:4~5		
Max. Aggregate Size	Dia.20 mm		
Conveying Hose Inner Diameter	Dia.64 mm		
Conveying Pressure	0.2-0.4MPa(29-58PSI)		
Air Consumption	10~12m <sup>3</sup> /min(357-430CFM)		
Material Charging Height	1.1m		
Rotor Speed	11r/min		
Electric Motor	7.5kW,Y132M-4,IP55		
Vibrator Electric Motor	0.15kW,XVM-A1.5-2		
Available Voltage	220V,380V, 440V,660V 50Hz/60Hz		
Overall Dimension(length×width×height)	1.65×0.9×1.25m		
Net Weight	900kg		

#### Air motor drive:

Output Capacity	5-9m <sup>3</sup> /h		
Max. Horizontal Conveying Distance	200m		
Suitable Mix Ratio(Cement/Sand)	≤1:4~5		
Max. Aggregate Size	Dia.20 mm		
Conveying Hose Inner Diameter	Dia.64 mm		
Conveying Pressure	0.2-0.4MPa(29-58PSI)		
Air Consumption for conveying material	10~12m <sup>3</sup> /min(357-430CFM)		
Material Charging Height	1.1m		

Version: Aug.2012 Copyright@Gaode Equipment Co., Ltd.

Rotor Speed	6-11r/min		
Air Motor	TMH8A		
Air pressure for air motor	0.5Mpa		
Air consumption for air motor	10 m <sup>3</sup> /min/357CFM		
Vibrator	OR100,oil		
Overall Dimension(length×width×height)	1.65×0.9×1.25m		
Net Weight	900kg		

#### Diesel drive:

Output Capacity	6-9m <sup>3</sup> /h		
Max. Horizontal Conveying Distance	200m		
Suitable Mix Ratio(Cement/Sand)	≤1:4~5		
Max. Aggregate Size	Dia.20 mm		
Conveying Hose Inner Diameter	Dia.64 mm		
Conveying Pressure	0.2-0.4MPa(29-58PSI)		
Air Consumption	10~12m <sup>3</sup> /min(357-430CFM)		
Material Charging Height	1.1m		
Rotor Speed	7.5-11r/min		
Diesel Engine	20hp,2200rpm, Radiator Cooling		
Diesel Engine Starting	Electric start		
Clutch Type in Diesel Engine	Automatic Clutch		
Air Vibrator	OR100,Oli		
Overall Dimension(length×width×height)	2.66×1.11×1.50m		
Net Weight	950kg		

#### **Certificate:**

CE AND ISO9001-2008





A complete set of GZ-9 shotcrete machine:

No.	Description	Quantity	Unit	Remarks
1	GZ-9 Main Machine	1	set	
2	Nozzle Assy.	1	set	
3	Conveying Hose, ID64mm, 50ft.Length	1	piece	
4	water hose with hose hoop	1	piece	
5	Rubber Hose Joint	3	piece	Fitting
6	Quick Coupling	3	piece	
7	Upper Sealing Plate	1	piece	
8	Lower Sealing Plate	1	piece	

#### **Our Spare parts:**



# Picture Electric drive:





## Diesel drive:







Version: Aug.2012

## **Application:**





# Gaode Equipment Co., Ltd.

Add: No.9, Building 14, Yard No.4, Fengqing Road, Jinshui District, Zhengzhou,

Henan China P.C.: 450000

Tel: +86-371-55951210 Fax: +86-371-63526676 Email: info@gaodetec.com Web: www.gaodetec.com