

Specifications

Small size , light weight
Long life
Easy handling
delivery time within 15 working days

BW-150 Drilling rig mud pump :

BW-150 drilling rig mud pump is one of the principle quipment for geological drilling. It delivers the enough volume circulating mud water of desired characteristic under pressure into the well to bring the rock clastic up to the ground, to cool the drill bit to lubricate the drill tool and to protect the wall of the well, so the function of mud pump affect the efficiency of drilling and safety in production direct .BW-150 Mud pump is a horizontal, triplex,single acting reciprocating piston pump ,which has eight speeds to get various output volume. It is capable of delivering circulation mud water required in small bore core drill ,ling 1000-1500 meter deep with diamond bit. The pump can be driven by electromotor or diesel engine according to the requirement of the customer in order.

Technical Data :

Туре	HorizontalTriplex Reciprocating Acting piston pump							
Stroke	70mm							
Bore	70mm							
handle position	1	2	3	4	1	2	3	4
Pump speed(s.p.m)	222	130	86	57	183	107	71	47
Output volume(I.p.m)	150	90	58	38	125	72	47	32
Discharge pressure(MPa)	1.8	3.2	4.8	7	2.3	4	6	7
Input power	7.5Kw							
input speed(r.p.m)	1500T/Min							
Max .suction head	2.5m							
Inside diameter of suction pi ping	51mm							
Inside diameter of discharge piping	25mm							
Weight	516Kg(With electromotor Y132M-4-B3) 630Kg(With diesel engine Z S1105)							
Overall dimensions(L*W*H)	1925*795*1150mm(With electromotor) 1840*795*995mm(With d iesel engine)							

